Hardware FlexES Control FX10 basic configuration, with software support for 5 loops

Art.Nr.: SEE808393



Hardware FlexES Control FX10 basic configuration, with software support for 5 loops.

Features:

Combinable loop/spur technology with decentralized intelligence
Freely configurable functionality of modules
4 free programmable potential free contacts and 1 output for alarm transmission unit (ATU)
Increased availability via emergency mode function of the loop modules
Emergency mode for monitored areas up to 48,000 m² or more than 512 fire detectors acc. to the German Planning standard VDE 0833 and/or VdS 2095.
USB, Ethernet, RS 485, TTY interfaces onboard
Direct output of the proprietary EDP communications protocol (Data Protocol) via interface RS 485
Operation of loop-powered alarm signaling devices (optical/acoustic/voice) in different alarm zones via esserbus-PLus
Cascadable power supply to 450 W according to

EN 54-4
Loop length up to 3.5 km (esserbus)
Operation of different input/output gateways
Integrated interfaces for operation of required fire brigade periphery, e.g. fire brigade indicating panel, fire brigade operating unit
Event memory with 10,000 entries
Operation of VdS-approved wireless components with convenient field intensity measurement
Parameterization, calibration and programming directly via USB
Galvanic isolation of analog loops possible

Specification

Length: cm 0
Width: cm 0
Height: cm 0
Volume: cc 0
Weight: kg

Domeyer GmbH & Co. KG
Konsul-Smidt-Str. 15, 28217 Bremen
Tel. 0421-3 77 88-0
Fax 0421-3 77 88-88
info@domeyer.eu
www.domeyer.eu