

## Dry Suit VIKING™ HDS

---

Art.Nr.: HA200004

---



---

Dry Suit VIKING™ HDS.

Material: Nitecs (HNBR rubber), lining: two-way stretch knitted black polyester.

Weight: 1050 g/m<sup>2</sup> ± 100 g.

Colour: All black.

Seams: Internal seams stitched together with an elastic tape for security. External seams vulcanised with a 25 mm rubber tape, ensuring watertight seams.

Reinforcements: Additional layer of Nitecs. The shoulder and zipper areas are reinforced. The trouser area is also protected and extends around the thighs down to the knees and down the front of the legs and over the boots.

Zipper: Back entry, heavy duty, 90 cm.

Valves: Standard configuration includes Viking Hazmat inlet valve with additional manual shut off function for emergency situations (central chest), Viking X2 exhaust valve (upper left arm), connection hose.

Latex cuffs and latex neckseal, Nitecs rubber boots with a heavy duty non slip flexible HDS rubber outsole and heel fin retainer. Suspenders, carry bag, user manual, repair kit, zip care materials come with each suit.

Viking HDS suits MUST be fitted with a hood for diving in contaminated water conditions.

Recommendation: Magnum HDS hood (made of the suit material nitecs).

Other options and accessories on request.

EN 14225-2:2005 Standard.

Sizes: 00 - 05 (S - XXXL), wide sizes: 01 - 04 (M - XXL), double wide sizes: 01 - 04 (M - XXL).

Link: <http://www.domeyer.eu/footer/downloads.html>

---

**Specification**

Volume: cc 0