Dry Suit VIKING™ VTS

Art.Nr.: HA200006



Dry Suit VIKING™ VTS.
Material: Trilaminate construction. Three material options are available as follows:
1.) 450 g/m² Cordura textured outer / Butyl midply / Polyester inner. Light and strong. Good puncture and abrasion resistance.
2.) 350 g/m² Nylon outer / Butyl midply / Nylon inner. Lighter and more flexible than Cordura. Equally good puncture and abrasion resistance. Smooth close knit exterior surface.
3.) 400 g/m² Polyester outer / Butyl midply / Polyester inner. Softer warmer feel than nylon. Good puncture and abrasion resistance.
Colour: All black.
Seams: External seams stitched together. Internal seams are chemically treated, an uncured rubber tape is applied to the seams using heat and pressure. Finally the suit is placed inside a vulcaniser whereby the rubber tape becomes cured into the material surface (""Vulca Seam technology "").
Reinforcement: Knee pads are fitted to the legs above and below the knees.
Zipper: With back entry, MD 90 cm or with front entry. MD 85/90 cm.
Valves: Standard configuration includes Viking Push protected inlet valve (central chest), Viking low profile adjustable exhaust valve (upper left arm), connection hose.
Latex cuffs and latex neckseal, rubber coated 5 mm neoprene boots with non slip outsole and heel fin retainer. Suspenders, carry bag, user manual, repair kit, zip care materials come with each suit.
Other options and accessories on request.
EN 14225-2:2005 Standard.
Sizes: 00 - 04 (S - XXL), wide sizes: 00 - 04 (S - XXL), double wide sizes: 00 - 04 (S - XXL).
Link: http://www.domeyer.eu/footer/downloads.html

Specification

Volume: cc 0

Domeyer GmbH & Co. KG
Konsul-Smidt-Str. 15, 28217 Bremen
Tel. 0421-3 77 88-0
Fax 0421-3 77 88-88
info@domeyer.eu
www.domeyer.eu