Breathing Air Compressor PE 200/250/300 TE

Art.Nr.: HA100006



Portable for mobile use
The PE 200-/250-/300-series offers a particularly good liaison of price and delivery performance. On the basis of the compact design can be transported the equipment easily and are loaded in a vessel. The oil pump allow a angle of inclination of up to 15°. So is the plant row for use on ships

Robust compressor block
- Piston rings made of a newly developed hightech synthetic material offer outstanding wear values.
- Oil cooling in the final compression stage for minimal wear and tear and for a longer life.
- Interstage and afterstage coolers made of stainless steel against corrosion.
- Robust low pressure oil pump with oil filter for effective lubrication and extended oil change intervals.

The following models are available:
PE 200 TE: delivery performance: 200l/min, filtersystem P21, motor three-phase 400 V, 50 Hz
PE 250 TE: delivery performance: 250l/min, filtersystem P21, motor three-phase 400 V, 50 Hz
PE 300 TE: delivery performance: 300l/min, filtersystem P21, motor three-phase 400 V, 50 Hz

Weight/Dimensions: L x W x H in cm : appr. 130 kg / appr. 110 x 52 x 57
When ordering please specify the desired operating pressure (225 bar or 330 bar)

Furthermore, the following options are possible:
- other operating voltage / frequency
- motor protection switch, including connection cable

- V2 electrical control, including connection cable
- V3 electrical control, including automatic condensation drain and end pressure switch
- V4 electrical control, including automatic condensation drain and SECURUS
- condensate collection system 10l
- B-Timer
- filter system P 31, P 41, P 42
- filling 2 x 200 bar
- filling 2 x 300 bar
- filling 1x 300/1 x 200 bar (changeover, not for P 31 filter system)

Specification

Volume: cc 0

Domeyer GmbH & Co. KG
Konsul-Smidt-Str. 15, 28217 Bremen
Tel. 0421-3 77 88-0
Fax 0421-3 77 88-88
info@domeyer.eu
www.domeyer.eu