High pressure extinguishing device HNE HiPress Vario 10 RT+SD

Art.Nr.: 110377



High pressure extinguisher HNE HiPress Vario 010 RT admitted to be used as a special extinguisher following EN 3 for electrical installations up to 1000 V.

Ideal for first attack in housing, fires, fires, vehicle fires and damping-down (fire classes A and B).
The throw up to 16 m allows a large safety margin, extinguishing agent jet with pistol without check dosed, constant operating pressure during the entire deletion. Minimal maintenance and upkeep costs, container and connections made of corrosion resistant material, suitable for use with seawater.
The variable adjustment of the air flow enables different depending on the application condition of the foam blanket. Swiveling allows fighting the fire from a safe distance or metered cover a large area.

Technical specifications:

-Rating 21 A when using water or a minimum 27 A, 233 B hydrogenated at 6% addition of AFFF 6% foaming agent (depending on the used foaming agent).

-Filling volume 10 l
-Operating pressure max. 34 bar
-Flow compact jet / spray approximately 27/10 l / min
-Function takes about 24/63 sec
-Throw max.1 6/6 m

-Dimensions (HxØ): 49.0 x 20.0 cm
-Weight: 15,2 kg (empty).

Supplied with swiveling nozzle, backpack frame and compressed air cylinder 2 l / 300 bar

Specification

Volume: cc 0

Domeyer GmbH & Co. KG
Konsul-Smidt-Str. 15, 28217 Bremen
Tel. 0421-3 77 88-0
Fax 0421-3 77 88-88
info@domeyer.eu
www.domeyer.eu