

## Breathing protection monitoring table DrägerMan PSS Merlin

---

Art.Nr.: 3351145

---



---

### Dräger PSS® Merlin®

The control board can process and control up to 12 breathing apparatus wearers simultaneously in which two positions on the board are provided for the rescue party. The activation of the data transceiver is done automatically by commissioning of the breathing apparatus, i.e. when Bodyguard II or Bodyguard 7000 is pressurized. The communication between the radio modem and the control board is started by inserting the key identifier/personal tags of the modems into the panel.

Following information are displayed on the monitoring table (amongst others):

- current tank pressure and low pressure warning
- dead man- alarm and manually controlled distress alert
- retreat signal and acknowledgment of the evacuation order by the ba-wearer
- temperature locally (only Bodyguard II)

Following signals can be sent via the control board (amongst others):

- evacuation order
- acknowledgment of Motionless alarm and manual distress alert
- retreat signal to the ba set wearer

Scope of supply Dräger PSS Merlin:

Contains:

- monitoring panel Dräger PSS Merlin
- Instructions
- Delivery including 2 NiMH batteries 7.2 V
  
- (BxHxT) 450x780x70 mm
- weight: approx 7,5 kg

---

### Specification

Length: cm 0

Width: cm 0

Height: cm 0

Volume: cc 0

Weight: kg