

Video Surface Control Case (Two Diver) with Monitor, Video & Light Control & DVR and Communicator.

Art.Nr.: TT16189



Video Surface Control Case (Two Diver) with Monitor, Video & Light Control & DVR and Communicator.

Ext. Power supply: 100-260 VAC, 50/60 Hz.

Int. Power supply: 24 VDC rechargeable battery with battery status indication, UPS function.

Battery life:

20 hours - two diver comms only

2 hours - two divers video & DVR

1 hour - one diver light & video & DVR.

Monitor: 10,4" Daylight Monitor, 1000 candela.

The Monitor view is selectable between one channel or two channels (picture and picture PAP or picture in picture PIP).

Light control: 100% dimmable per diver, max 30 watts, 12-30 VDC.

Video out: 1 per diver, 1Vpp/75 Ohm.

DVR: Solid State HD recording, H264,avi 720×576 pixels@25 fps and 944×576 pixels@ 20 fps.

Video control: Video transmission over twisted pair or coax, auto-tune to 600 m, 32 VDC (12,15,24 VDC optional).

DVR control: Panel keypad control & mouse.

Recording time: 100 hrs@ 960H best, 1,2 Gb / hr. (120 Gb SSD-HD).

Recording channel: 2 channel, per channel record button.

Ext. speaker: Amplifier 10W/4-8 Ohm with volume control.

Video file: Retrievable with USB memory stick (*.avi) or connection to PC via LAN.

Audio Out: 1 per diver signal of 1Vpp.

Diver to diver: Cross-talk switch, full duplex (4 wire).

Diver volume control: Per diver.

Communication: 2 wire – simplex, 4 wire – full duplex.

Connection to network.

Text and Data Overlay.

Dimensions: 546 x 350 x 247mm.

Weight: 16,8 Kg.

Specification

Volume: cc 0