Video Surface Control Case (Two Diver) with Monitor, Video & Light Control & DVR and Communicator.

Art.Nr.: TT16189



Video Surface Control Case (Two Diver) with Monitor, Video & Light Control & DVR and Communicator.
Ext. Power supply: 100-260 VAC, 50/60 Hz.
Int. Power supply: 24 VDC rechargeable battery with battery status indication, UPS function.
Battery life:
20 hours - two diver comms only
2 hours - two divers video & DVR
1 hour - one diver light & video & DVR.
Monitor: 10,4” Daylight Monitor, 1000 candela.
The Monitor view is selectable between one channel or two channels (picture and picture PAP or picture in picture PIP).
Light control: 100% dimmable per diver, max 30 watts, 12-30 VDC.
Video out: 1 per diver, 1Vpp/75 Ohm.
DVR: Solid State HD recording, H264,avi 720×576 pixels@25 fps and 944×576 pixels@ 20 fps.
Video control: Video transmission over twisted pair or coax, auto-tune to 600 m, 32 VDC (12,15,24 VDC optional).
DVR control: Panel keypad control & mouse.
Recording time: 100 hrs@ 960H best, 1,2 Gb / hr. (120 Gb SSD-HD).
Recording channel: 2 channel, per channel record button.
Ext. speaker: Amplifier 10W/4-8 Ohm with volume control.
Video file: Retrievable with USB memory stick (*.avi) or connection to PC via LAN.
Audio Out: 1 per diver signal of 1Vpp.
Diver to diver: Cross-talk switch, full duplex (4 wire).
Diver volume control: Per diver.

Communication: 2 wire – simplex, 4 wire – full duplex.
Connection to network.
Text and Data Overlay.
Dimensions: 546 x 350 x 247mm.
Weight: 16,8 Kg.

Specification

Volume: cc 0

Domeyer GmbH & Co. KG
Konsul-Smidt-Str. 15, 28217 Bremen
Tel. 0421-3 77 88-0
Fax 0421-3 77 88-88
info@domeyer.eu
www.domeyer.eu