Personal entry meter Pac 6500

Art.Nr.: 8326341



Dräger Pac 6500 The personal entry meter Pac 6500 is approved according to cCSAus, ATEX and IECEx for Zone 0, T4. For reliable alarming, you can choose between 4 different DrägerSensors XXS. The device is configured according to customer requirements and comes with an instruction manual (10 languages). - fixed crocodile clip - triple alarm: optical 360 ° alarm LEDs, acoustic (90 dBA), vibration - gas inlet opening from top and front - language-free display - D-Light (confidence signal) - shockproof and robust housing - sensor identification by colored and Written marking - easily exchangeable robust dust filter - event and data logger - exchangeable battery - compatible with the Dräger X-dock and Dräger Bump Test Station - customer-specific settings - optional: calibration certificate Possible sensors: DrägerSensor XXS H2S LC, DrägerSensor XXS CO LC, DrägerSensor XXS O2, DrägerSensor XXS SO2 gas meter: - Dimensions: 60 x 84 x 20 mm - Weight: 106 g (113 g with clamp) - Degree of protection: IP68

Specification

Height: cm 0
Volume: cc 0
Weight: kg

Domeyer GmbH & Co. KG
Konsul-Smidt-Str. 15, 28217 Bremen
Tel. 0421-3 77 88-0
Fax 0421-3 77 88-88
info@domeyer.eu
www.domeyer.eu